

1.74 両面非球面設計

SVスーパー74WAS UV400

NEW

ビューティフルコート

超硬質+耐熱コーティング

プラチナコート

超硬質コーティング

つるつるコート

超撥水コーティング

耐衝撃コーティング[セーフティコート]標準
新UVカット標準

基本仕様

屈折率	1.74	設計	両面非球面設計
比重	1.47	透過率	98.5%
アッベ数	33		

NEW

Beautiful
BEAUTIFUL COAT LENS

キズ+熱+汚れに抜群に強い
超硬質+耐熱 ビューティフルコート誕生

ビューティフルコート …全て特注となります

プラチナコート … 在庫範囲 (プラチナコート)

度数 (-)	球面	乱視 (-)															
		0.25	0.50	0.75	1.00	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	4.00
0.00																	
.25																	
.50																	
.75																	
1.00																	
.25																	
.50																	
.75																	
2.00																	
.25																	
.50																	
.75																	
3.00																	
.25																	
.50																	
.75																	
4.00																	
.25																	
.50																	
.75																	
5.00																	
.25																	
.50																	
.75																	
6.00																	
.25																	
.50																	
.75																	
7.00																	
.25																	
.50																	
.75																	
8.00																	
.25																	
.50																	
.75																	
9.00																	
.25																	
.50																	
.75																	
10.00																	
.25																	
.50																	
.75																	
11.00																	
.25																	
.50																	
.75																	
12.00																	
.25																	
.50																	
.75																	
13.00																	
.25																	
.50																	
.75																	
14.00																	
.25																	
.50																	
.75																	
15.00																	

つるつるコート 在庫範囲

度数 (-)	球面	乱視 (-)															
		0.25	0.50	0.75	1.00	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	4.00
2.00																	
.25																	
.50																	
.75																	
3.00																	
.25																	
.50																	
.75																	
4.00																	
.25																	
.50																	
.75																	
5.00																	
.25																	
.50																	
.75																	
6.00																	
.25																	
.50																	
.75																	
7.00																	
.25																	
.50																	
.75																	
8.00																	
.25																	
.50																	
.75																	
9.00																	
.25																	
.50																	
.75																	
10.00																	
.25																	
.50																	
.75																	
11.00																	
.25																	
.50																	
.75																	
12.00																	
.25																	
.50																	
.75																	
13.00																	
.25																	
.50																	
.75																	
14.00																	
.25																	
.50																	
.75																	
15.00																	

S-10.00以上は0.50単位となりますので、ご注意下さい

特注加工	ビューティフルコート プラチナコート
カラー	○ アリアーテ 対応 レイバンカラー・見本色不可
プリズム	○ 3△まで
偏心	×
外径指定	×
厚み指定	×
UVカット	UV400標準

特注加工	つるつるコート
カラー	○ アリアーテ 対応 レイバンカラー・見本色不可
プリズム	×
偏心	×
外径指定	×
厚み指定	×
UVカット	UV400標準