

1.55AS設計(Blue Light Control & Technology)

# Blue Tech 55AS UV PREMIUM

つるつるコート 超撥水コーティング

ブルーテック

静電気防止コート付

基本仕様

屈折率	1.55	設計	非球面設計
比重	1.28	透過率	93%
アッベ数	38		

つるつるコート ... 在庫範囲

度数 (-)	球面	乱視 (-)					
		0.25	.50	.75	1.00	.25	.50
0.00							
.25							
.50							
.75							
1.00							
.25							
.50							
.75							
2.00							
.25							
.50							
.75							
3.00							
.25							
.50							
.75							
4.00							
.25							
.50							
.75							
5.00							
.25							
.50							
.75							
6.00							
.25							
.50							
.75							
7.00							
.25							
.50							
.75							
8.00							

度数 (+)	球面	乱視 (+)					
		0.25	.50	.75	1.00	.25	.50
0.00	X						
.25							
.50							
.75							
1.00							
.25							
.50							
.75							
2.00							
.25							
.50							
.75							
3.00							
.25							
.50							
.75							
4.00							

混合乱視 (MIX)						
C	0.50	.75	1.00	.25	.50	2.00
S+						
0.25						
0.50						
0.75						
1.00						
1.25						
1.50						
1.75						

常備在庫レンズのみの設定となります。  
カラー 外径指定等特注加工は  
お受けできませんのでご注意ください。

特注加工

カラー	×
プリズム	×
偏心	×
外径指定	×
厚み指定	×
UVカット	UV PREMIUM (400nm99%カット 420nm60%カット)