

Blue Tech 67AS RX

UV PREMIUM

ブルーテック

静電気防止コート付

基本仕様

屈折率	1.67	設計	非球面設計
比重	1.35	透過率	93%
アップ数	32		

プラチナ DUV コート

つるつるコート

全て特注となります

度数 (-)	球面	乱視 (-)															
		0.25	.50	.75	1.00	.25	.50	.75	2.00	.25	.50	.75	3.00	.25	.50	.75	4.00
0.00																	
.25																	
.50																	
.75																	
1.00																	
.25																	
.50																	
.75																	
2.00																	
.25																	
.50																	
.75																	
3.00																	
.25																	
.50																	
.75																	
4.00																	
.25																	
.50																	
.75																	
5.00																	
.25																	
.50																	
.75																	
6.00																	
.25																	
.50																	
.75																	
7.00																	
.25																	
.50																	
.75																	
8.00																	
.25																	
.50																	
.75																	
9.00																	
.25																	
.50																	
.75																	
10.00																	
.25																	
.50																	
.75																	
11.00																	
.25																	
.50																	
.75																	
12.00																	

特注加工

カラー	○アリアーテ 対応 推奨濃度25%以上 レイバンカラー・見本色不可
プリズム	○ 3△まで ●印はお問合せ下さい
偏心	×
外径指定	×
厚み指定	○
UVカット	UV PREMIUM (400nm99%カット 420nm60%カット)

※カラー染色についてのご注意

度数により色調が変化します

従来のレンズに比べ照明による色調の変化が occurs

ハーフ染色は基材の色の干渉をうけますのでご注意ください

アリアーテ見本に比べくすみが多くなります