

# PI-III

マルチコート

## 基本仕様

屈折率	1.80	設計	球面設計
比重	3.54	透過率	99.0%
アップ数	35		

## 製作範囲表

在庫範囲 (無色)

度数 (-)	球面	乱視 (-)																		
		0.25	.50	.75	1.00	.25	.50	.75	2.00	.25	.50	.75	3.00	.25	.50	.75	4.00			
3.00																				
.25																				
.50																				
.75																				
4.00																				
.25																				
.50																				
.75																				
5.00																				
.25																				
.50																				
.75																				
6.00																				
.25																				
.50																				
.75																				
7.00																				
.25																				
.50																				
.75																				
8.00																				
.25																				
.50																				
.75																				
9.00																				
.25																				
.50																				
.75																				
10.00																				
.25																				
.50																				
.75																				
11.00																				
.25																				
.50																				
.75																				
12.00																				
.25																				
.50																				
.75																				
13.00																				
.25																				
.50																				
.75																				
14.00																				
.25																				
.50																				
.75																				
15.00																				
.25																				
.50																				
.75																				
16.00																				
.25																				
.50																				
.75																				
17.00																				
.25																				
.50																				
.75																				
18.00																				
.25																				
.50																				
.75																				
19.00																				
.25																				
.50																				
.75																				
20.00																				

## カラー種類

ブラウン	15% 25% 50%
------	-------------

カラー：色抜けの心配が無いコーティング(蒸着)タイプ

## 特注加工

カラー	<input type="radio"/> 上記カラー種類にて設定
プリズム	<input type="radio"/> (S+C=-10.00D迄) 3△まで可
偏心	<input type="radio"/> (S+C=-10.00D迄はプリズム換算) 3△まで可
外径指定	<input checked="" type="checkbox"/>
厚み指定	<input checked="" type="checkbox"/>
ツボクリ	<input type="radio"/>