

PI-Ⅲ AS

マルチコート

基本仕様

屈折率	1.80	設計	非球面設計
比重	3.54	透過率	99.0%
アップ数	35		

製作範囲表 全て特注となります

度数 (-)	球面	乱 視 (一)															
		0.25	.50	.75	1.00	.25	.50	.75	2.00	.25	.50	.75	3.00	.25	.50	.75	4.00
3.00																	
.25																	
.50																	
.75																	
4.00																	
.25																	
.50																	
.75																	
5.00																	
.25																	
.50																	
.75																	
6.00																	
.25																	
.50																	
.75																	
7.00																	
.25																	
.50																	
.75																	
8.00																	
.25																	
.50																	
.75																	
9.00																	
.25																	
.50																	
.75																	
10.00																	
.25																	
.50																	
.75																	
11.00																	
.25																	
.50																	
.75																	
12.00																	
.25																	
.50																	
.75																	
13.00																	
.25																	
.50																	
.75																	
14.00																	
.25																	
.50																	
.75																	
15.00																	
.25																	
.50																	
16.00																	

S-15.00以上は0.50単位となりますので、ご注意下さい

カラー種類

ブラウン	15%	25%	50%
------	-----	-----	-----

カラー：色抜けの心配が無いコーティング(蒸着)タイプ

特注加工

カラー	○ 上記カラー種類にて設定
プリズム	○ 詳細はお問い合わせ下さい
偏心	×
外径指定	×
厚み指定	×
ツボクリ	○