

1.55 球面設計

PL1.55 UV400

内面マルチ ※

ハードマルチ

※ 内面マルチ

・表面：ハードコート

・裏面：ハードマルチ+つるつるコート付

新UVカット標準

基本仕様

屈折率	1.55	設計	球面設計
比重	1.28	透過率	98.5%
アップベ数	38		

内面マルチ …全て特注となります

ハードマルチ …在庫範囲

度数 (-)	球面	乱視 (-)										
		0.25	.50	.75	1.00	.25	.50	.75	1.00	.25	.50	.75
0.00												
.25												
.50												
.75												
1.00												
.25												
.50												
.75												
2.00												
.25												
.50												
.75												
3.00												
.25												
.50												
.75												
4.00												
.25												
.50												
.75												
5.00												
.25												
.50												
.75												
6.00												
.25												
.50												
.75												
7.00												
.25												
.50												
.75												
8.00												

度数 (+)	球面	乱視 (+)										
		0.25	.50	.75	1.00	.25	.50	.75	1.00	.25	.50	.75
0.00												
.25												
.50												
.75												
1.00												
.25												
.50												
.75												
2.00												
.25												
.50												
.75												
3.00												
.25												
.50												
.75												
4.00												
.25												
.50												
.75												
5.00												

混合乱視 (MIX)												
C-	S+	0.25	.50	.75	1.00	.25	.50	.75	1.00	.25	.50	.75
0.25												
.50												
.75												
1.00												
.25												
.50												
.75												
1.00												
.25												
.50												
.75												
2.00												
.25												
.50												
.75												
3.00												
.25												
.50												
.75												
4.00												
.25												
.50												
.75												
5.00												
.25												
.50												
.75												
6.00												
.25												
.50												
.75												
7.00												
.25												
.50												
.75												
8.00												

注1. 上記マイナス度数で、特注研磨条件(プリズム・偏心等)が付く場合は
基準外径が70mmとなりますので、ご注意ください。

特注加工

カラー	○ アリアーテ レイバンカラー (G15、G31、#3) 対応 見本色対応
プリズム	○ 3△まで ※1
偏心	○ (プリズム換算) 3△まで ※1
外径指定	○ 〈縮小〉 +、MIX範囲 基準径～最小55mm(1mm単位) 〈拡大〉 () 内のサイズまで製作可(1mm単位)
厚み指定	○
UVカット	UV400標準

※1. 基準外径及び外径縮小時のプリズム・偏心可能量となります。
外径拡大時のプリズム・偏心可能量につきましては、お問い合わせ下さい。

原産国 無色 / 日本・中国
カラー / 日本

2019.03