

1.56 非球面設計 (超耐衝撃素材・ハイインパクト)

Hi-Vex[®] AS UV400

基本仕様

屈折率	1.56	設計	非球面設計
比重	1.25	透過率	98.5%
アッペ数	44		

コート名称	機能			
	耐キズ	超撥水	防帯電	耐熱
つるつる	○	○	-	-
				光線カット UV

製品在庫範囲 (つるつる)

度数 (-)	球面	乱視 (-)				
		0.25	.50	.75	1.00	2.00
0.00						
.25						
.50						
.75						
1.00						
.25						
.50						
.75						
2.00						
.25						
.50						
.75						
3.00						
.25						
.50						
.75						
4.00						
.25						
.50						
.75						
5.00						
.25						
.50						
.75						
6.00						

度数 (+)	球面	乱視 (+)				
		0.25	.50	.75	1.00	2.00
0.00	×					
.25						
.50						
.75						
1.00						
.25						
.50						
.75						
2.00						
.25						
.50						
.75						
3.00						
.25						
.50						
.75						
4.00						

混合乱視 (MIX)					
C-	乱視 (+)				
	0.25	.50	.75	1.00	2.00
S+					
0.25					
.50					
.75					
1.00					
.25					
.50					
.75					
1.00					
.25					
.50					
.75					
1.50					
1.75					

特注加工

カラー	○	アリアーテ対応、レイバンカラー (G15、G31、#3) 対応 見本色対応
プリズム	×	
偏心	×	
外径指定	×	
スライス加工	×	
厚み指定	×	
UVカット		UV400標準
玉型カット	○	
範囲外	×	

原産国：日本、中国
2020.08

