

1.55 球面設計

PL1.55 UV400

基本仕様

屈折率	1.55	設計	球面
比重	1.28	透過率	98.5%
アッベ数	38		

コート名称	機能				
	耐キズ	超撥水	防帯電	耐熱	光線カット
内面マルチ	-	裏のみ○	-	-	UV
ハードマルチ	-	-	-	-	UV

製品在庫範囲 (ハードマルチ)

度数 (-)	球面				
	0.25	.50	.75	1.00	2.00
0.00					
.25					
.50					
.75					
1.00					
.25					
.50					
.75					
2.00					
.25					
.50					
.75					
3.00					
.25					
.50					
.75					
4.00					
.25					
.50					
.75					
5.00					
.25					
.50					
.75					
6.00					
.25					
.50					
.75					
7.00					
.25					
.50					
.75					
8.00					

度数 (+)	球面				
	0.25	.50	.75	1.00	2.00
0.00					
.25					
.50					
.75					
1.00					
.25					
.50					
.75					
2.00					
.25					
.50					
.75					
3.00					
.25					
.50					
.75					
4.00					

混合乱視 (MIX)					
C-	.50	.75	1.00	.25	2.00
S+	0.25				
	0.50				
	0.75				
	1.00				
	1.25				
	1.50				
	1.75				

特注加工

カラー	○ アリアーテ対応、レイバンカラー (G15、G31、#3) 対応 見本色対応
プリズム	×
偏心	×
外径指定	×
スライス加工	×
厚み指定	×
UVカット	UV400標準
玉型カット	○
範囲外	×

原産国：在庫品：中国

特注品：日本

2020.08

