

SVスーパー74AS UV400

基本仕様

屈折率	1.74	設計	非球面設計
比重	1.47	透過率	98.5%
アッペ数	33		

コート名称	機能				
	耐キズ	超撥水	防帯電	耐熱	光線カット
つるつる	○	○	-	-	UV
プラチナ	◎	◎	○	-	UV
ブルークリア	◎	◎	○	○	UV・青色
ビューティフル	◎	◎	○	○	UV
ボードン					UV

度数 (-)	球面	乱視 (-)															
		0.25	.50	.75	1.00	.25	.50	.75	2.00	.25	.50	.75	3.00	.25	.50	.75	4.00
0.00																	
.25																	
.50																	
.75																	
1.00																	
.25																	
.50																	
.75																	
2.00																	
.25																	
.50																	
.75																	
3.00																	
.25																	
.50																	
.75																	
4.00																	
.25																	
.50																	
.75																	
5.00																	
.25																	
.50																	
.75																	
6.00																	
.25																	
.50																	
.75																	
7.00																	
.25																	
.50																	
.75																	
8.00																	
.25																	
.50																	
.75																	
9.00																	
.25																	
.50																	
.75																	
10.00																	
.25																	
.50																	
.75																	
11.00																	
.25																	
.50																	
.75																	
12.00																	
.25																	
.50																	
.75																	
13.00																	
.25																	
.50																	
.75																	
14.00																	
.25																	
.50																	
.75																	
15.00																	
.25																	
.50																	
.75																	
16.00																	
.25																	
.50																	
.75																	
17.00																	
.25																	
.50																	
.75																	
18.00																	

特注加工

カラー	<input type="radio"/> アリアーテ対応 レイバンカラー・見本色不可
プリズム	<input type="radio"/> 3△まで
偏心	<input checked="" type="checkbox"/> ×
外径指定	<input checked="" type="checkbox"/> ×
スライス加工	<input checked="" type="checkbox"/> ×
厚み指定	<input checked="" type="checkbox"/> ×
UVカット	UV400標準
玉型カット	<input type="radio"/> ○
範囲外	度数、プリズム、中間度数対応可 (お問合せください)

原産国：日本
2020.08

