

Blue Tech 55AS

UV PREMIUM

基本仕様

屈折率	1.55	設計	非球面設計
比重	1.28	透過率	93.0%
アッペ数	38		

コート名称	機能				
	耐キズ	超撥水	防帯電	耐熱	光線カット
つるつる	○	○	○	-	UV

製品在庫範囲 (つるつる)

度数 (-)	球面	乱視 (-)					
		0.25	.50	.75	1.00	.25	.50
0.00							
.25							
.50							
.75							
1.00							
.25							
.50							
.75							
2.00							
.25							
.50							
.75							
3.00							
.25							
.50							
.75							
4.00							
.25							
.50							
.75							
5.00							
.25							
.50							
.75							
6.00							
.25							
.50							
.75							
7.00							
.25							
.50							
.75							
8.00							

度数 (+)	球面	乱視 (+)					
		0.25	.50	.75	1.00	.25	.50
0.00	×						
.25							
.50							
.75							
1.00							
.25							
.50							
.75							
2.00							
.25							
.50							
.75							
3.00							
.25							
.50							
.75							
4.00							

混合乱視 (MIX)						
C	.50	.75	1.00	.25	.50	.75
S+						
0.25						
.50						
.75						
1.00						
.25						
.50						
.75						
2.00						
.25						
.50						
.75						
1.75						
2.00						

常備在庫レンズのみの設定となります。
カラー、外径指定等の特注加工はお受け
できませんのでご注意ください。

特注加工

カラー	×
プリズム	×
偏心	×
外径指定	×
スライス加工	×
厚み指定	×
UVカット	UV PREMIUM (400nm 99%カット、420nm60%カット)
玉型カット	○
範囲外	×