

1.74 両面非球面設計 (耐衝撃コーティング)

SVスーパー74WAS UV400

基本仕様

屈折率	1.74	設計	両面非球面設計
比重	1.47	透過率	98.5%
アッペ数	33		

コート名称	機能				
	耐キズ	超撥水	防帯電	耐熱	光線カット
つるつる	○	○	-	-	UV
プラチナ	◎	◎	○	-	UV
ブルークリア	◎	◎	○	○	UV・青色
ピュートイフル	◎	◎	○	○	UV
ボードン					UV

度数 (-)	球面	乱視 (-)																
		0.25	.50	.75	1.00	.25	.50	.75	2.00	.25	.50	.75	3.00	.25	.50	.75	4.00	
0.00																		
.25																		
.50																		
.75																		
1.00																		
.25																		
.50																		
.75																		
2.00																		
.25																		
.50																		
.75																		
3.00																		
.25																		
.50																		
.75																		
4.00																		
.25																		
.50																		
.75																		
5.00																		
.25																		
.50																		
.75																		
6.00																		
.25																		
.50																		
.75																		
7.00																		
.25																		
.50																		
.75																		
8.00																		
.25																		
.50																		
.75																		
9.00																		
.25																		
.50																		
.75																		
10.00																		
.25																		
.50																		
.75																		
11.00																		
.25																		
.50																		
.75																		
12.00																		
.25																		
.50																		
.75																		
13.00																		
.25																		
.50																		
.75																		
14.00																		
.25																		
.50																		
.75																		
15.00																		

特注加工

カラー	○ アリアーテ対応 レイバンカラー・見本色不可
プリズム	○ 3△まで
偏心	×
外径指定	×
スライス加工	○ (メガネでの薄型加工対応)
厚み指定	○
UVカット	UV400標準
玉型カット	○
範囲外	度数、プリズム、中間度数対応可 (お問合せください)

原産国：日本
2020.08

