

仕様

| | |
|------|------|
| 屈折率 | 1.55 |
| 比重 | 1.28 |
| アッペ数 | 38 |
| 設計 | 球面 |

対応コート

- ハードマルチ
- 内面マルチ (表) ハード (裏) ハードマルチ+つるつる

製作範囲表

在庫範囲 (ハードマルチ)

| 度数 (-) | 球面 | 乱視 (-) | | | | |
|-----------|----|--------|-----|-----|------|------|
| | | 0.25 | .50 | .75 | 1.00 | 2.00 |
| 0.00 | | | | | | |
| .25 | | | | | | |
| .50 | | | | | | |
| .75 | | | | | | |
| 1.00 | | | | | | |
| .25 | | | | | | |
| .50 | | | | | | |
| .75 | | | | | | |
| 2.00 | | | | | | |
| .25 | | | | | | |
| .50 | | | | | | |
| .75 | | | | | | |
| 3.00 | | | | | | |
| .25 | | | | | | |
| .50 | | | | | | |
| .75 | | | | | | |
| 4.00 | | | | | | |
| .25 | | | | | | |
| .50 | | | | | | |
| .75 | | | | | | |
| 5.00 | | | | | | |
| .25 | | | | | | |
| .50 | | | | | | |
| .75 | | | | | | |
| 6.00 | | | | | | |
| .25 | | | | | | |
| .50 | | | | | | |
| .75 | | | | | | |
| 7.00 | | | | | | |
| .25 | | | | | | |
| .50 | | | | | | |
| .75 | | | | | | |
| 8.00 | | | | | | |

| 度数 (+) | 球面 | 乱視 (+) | | | | |
|-----------|----|--------|-----|-----|------|------|
| | | 0.25 | .50 | .75 | 1.00 | 2.00 |
| 0.00 | | | | | | |
| .25 | | | | | | |
| .50 | | | | | | |
| .75 | | | | | | |
| 1.00 | | | | | | |
| .25 | | | | | | |
| .50 | | | | | | |
| .75 | | | | | | |
| 2.00 | | | | | | |
| .25 | | | | | | |
| .50 | | | | | | |
| .75 | | | | | | |
| 3.00 | | | | | | |
| .25 | | | | | | |
| .50 | | | | | | |
| .75 | | | | | | |
| 4.00 | | | | | | |

| C(-) | 混合乱視 (MIX) | | | | |
|------|------------|-----|------|-----|-----|
| | .50 | .75 | 1.00 | .25 | .50 |
| S(+) | | | | | |
| | 0.25 | | | | |
| | .50 | | | | |
| | .75 | | | | |
| | 1.00 | | | | |
| | | .25 | | | |
| | | .50 | | | |
| | | .75 | | | |

カラー

| | | |
|--------------------|---|--|
| アリアーテ | ○ | |
| レイバン G15・G31・#3 | ○ | |
| 見本色 | ○ | |
| リラックス | × | |

特殊加工

| | | |
|--------|----|----|
| 外径指定 | × | |
| プリズム | × | |
| 偏心 | × | |
| カーブ指定 | × | |
| UVカット | 標準 | ※1 |
| 厚み指定 | × | |
| 玉型カット | ○ | |
| スライス加工 | × | |

※1 UV400

原産国

在庫品：中国 特注品：日本