

PI-III

基本仕様

屈折率	1.80	設計	球面
比重	3.54	透過率	99.0%
アッペ数	35		

度数 (一)	球面	乱視 (一)														
		0.25	.80	1.00	.25	.50	.75	2.00	.25	.50	.75	3.00	.25	.50	.75	4.00
3.00																
.25																
.50																
.75																
4.00																
.25																
.50																
.75																
5.00																
.25																
.50																
.75																
6.00																
.25																
.50																
.75																
7.00																
.25																
.50																
.75																
8.00																
.25																
.50																
.75																
9.00																
.25																
.50																
.75																
10.00																
.25																
.50																
.75																
11.00																
.25																
.50																
.75																
12.00																
.25																
.50																
.75																
13.00																
.25																
.50																
.75																
14.00																
.25																
.50																
.75																
15.00																
.25																
.50																
.75																
16.00																
.25																
.50																
.75																
17.00																
.25																
.50																
.75																
18.00																
.25																
.50																
.75																
19.00																
.25																
.50																
.75																
20.00																

特注加工

カラー	<input type="radio"/> カラーマルチ対応 (ブラウン15%、25%)
プリズム	<input type="radio"/> 詳細はお問合せください
偏心	<input type="radio"/> 詳細はお問合せください
外径指定	<input checked="" type="checkbox"/> ×
スライス加工	<input checked="" type="checkbox"/> ×
厚み指定	<input checked="" type="checkbox"/> ×
玉型カット	<input type="radio"/> ○
範囲外	度数、プリズム、中間度数対応可 (お問合せください)
ツボクリ	<input type="radio"/> ○