

# T-SV SPF EC I 60SP PUV

T-SV SPF EC I 60SP PUV

プラスチック

単焦点

球面

1.60

## 仕様

屈折率	1.60
比重	1.31
アッペ数	42
設計	球面

## 対応コート

●PUV (超硬質+超撥水+近赤外線カット+裏面UVカット)

## 製作範囲表

度数 (-)	球面	乱視 (-)																		
		0.25	.50	.75	1.00	.25	.50	.75	1.00	.25	.50	.75	1.00							
0.00																				
.25																				
.50																				
.75																				
1.00																				
.25																				
.50																				
.75																				
2.00																				
.25																				
.50																				
.75																				
3.00																				
.25																				
.50																				
.75																				
4.00																				
.25																				
.50																				
.75																				
5.00																				
.25																				
.50																				
.75																				
6.00																				
.25																				
.50																				
.75																				
7.00																				
.25																				
.50																				
.75																				
8.00																				
.25																				
.50																				
.75																				
9.00																				
.25																				
.50																				
.75																				
10.00																				

度数 (+)	球面	乱視 (+)																		
		0.25	.50	.75	1.00	.25	.50	.75	1.00	.25	.50	.75	1.00							
0.00																				
.25																				
.50																				
.75																				
1.00																				
.25																				
.50																				
.75																				
2.00																				
.25																				
.50																				
.75																				
3.00																				
.25																				
.50																				
.75																				
4.00																				
.25																				
.50																				
.75																				
5.00																				
.25																				
.50																				
.75																				
6.00																				

C(-)	S(+)	混合乱視 (MIX)																		
		.50	.75	1.00	.25	.50	.75	1.00	.25	.50	.75	1.00								
0.25																				
.50																				
.75																				
1.00																				
.25																				
.50																				
.75																				
2.00																				
.25																				
.50																				
.75																				
3.00																				
.25																				
.50																				
.75																				
4.00																				
.25																				
.50																				
.75																				
5.00																				
.25																				
.50																				
.75																				
6.00																				

## カラー

アリアーテ	○	
レイバン G15・G31・#3	○	
見本色	○	
リラックス	×	

## 特殊加工

外径指定	○	※1
プリズム	○	※2
偏心	○	※3
カーブ指定	×	
UVカット	標準	
厚み指定	○	
玉型カット	○	
スライス加工	○	

- ※1 [縮小]  
(+, MIX範囲) 基準径~最小55mm (1mm単位)  
[拡大]  
可表記まで製作可 (1mm単位)
- ※2 3△まで可
- ※3 (プリズム換算) 3△まで可

原産国

日本