

T-SV SPF HG I74AS

T-SV SPF HG I74AS

プラスチック

単焦点

非球面

1.74

仕様

| | |
|------|------|
| 屈折率 | 1.74 |
| 比重 | 1.47 |
| アッベ数 | 33 |
| 設計 | 非球面 |

対応コート

●IRBインパクト（超硬質+近赤外線カット+ブルーライトカット+耐衝撃+静電気防止）

製作範囲表

| 度数 (-) | 球面 | 乱視 (-) | | | | | | | | | | | | | | | |
|-----------|----|--------|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|-----|-----|-----|------|
| | | 0.25 | .50 | .75 | 1.00 | .25 | .50 | .75 | 2.00 | .25 | .50 | .75 | 3.00 | .25 | .50 | .75 | 4.00 |
| 0.00 | | | | | | | | | | | | | | | | | |
| .25 | | | | | | | | | | | | | | | | | |
| .50 | | | | | | | | | | | | | | | | | |
| .75 | | | | | | | | | | | | | | | | | |
| 1.00 | | | | | | | | | | | | | | | | | |
| .25 | | | | | | | | | | | | | | | | | |
| .50 | | | | | | | | | | | | | | | | | |
| .75 | | | | | | | | | | | | | | | | | |
| 2.00 | | | | | | | | | | | | | | | | | |
| .25 | | | | | | | | | | | | | | | | | |
| .50 | | | | | | | | | | | | | | | | | |
| .75 | | | | | | | | | | | | | | | | | |
| 3.00 | | | | | | | | | | | | | | | | | |
| .25 | | | | | | | | | | | | | | | | | |
| .50 | | | | | | | | | | | | | | | | | |
| .75 | | | | | | | | | | | | | | | | | |
| 4.00 | | | | | | | | | | | | | | | | | |
| .25 | | | | | | | | | | | | | | | | | |
| .50 | | | | | | | | | | | | | | | | | |
| .75 | | | | | | | | | | | | | | | | | |
| 5.00 | | | | | | | | | | | | | | | | | |
| .25 | | | | | | | | | | | | | | | | | |
| .50 | | | | | | | | | | | | | | | | | |
| .75 | | | | | | | | | | | | | | | | | |
| 6.00 | | | | | | | | | | | | | | | | | |
| .25 | | | | | | | | | | | | | | | | | |
| .50 | | | | | | | | | | | | | | | | | |
| .75 | | | | | | | | | | | | | | | | | |
| 7.00 | | | | | | | | | | | | | | | | | |
| .25 | | | | | | | | | | | | | | | | | |
| .50 | | | | | | | | | | | | | | | | | |
| .75 | | | | | | | | | | | | | | | | | |
| 8.00 | | | | | | | | | | | | | | | | | |
| .25 | | | | | | | | | | | | | | | | | |
| .50 | | | | | | | | | | | | | | | | | |
| .75 | | | | | | | | | | | | | | | | | |
| 9.00 | | | | | | | | | | | | | | | | | |
| .25 | | | | | | | | | | | | | | | | | |
| .50 | | | | | | | | | | | | | | | | | |
| .75 | | | | | | | | | | | | | | | | | |
| 10.00 | | | | | | | | | | | | | | | | | |
| .25 | | | | | | | | | | | | | | | | | |
| .50 | | | | | | | | | | | | | | | | | |
| .75 | | | | | | | | | | | | | | | | | |
| 11.00 | | | | | | | | | | | | | | | | | |
| .25 | | | | | | | | | | | | | | | | | |
| .50 | | | | | | | | | | | | | | | | | |
| .75 | | | | | | | | | | | | | | | | | |
| 12.00 | | | | | | | | | | | | | | | | | |
| .25 | | | | | | | | | | | | | | | | | |
| .50 | | | | | | | | | | | | | | | | | |
| .75 | | | | | | | | | | | | | | | | | |
| 13.00 | | | | | | | | | | | | | | | | | |
| .25 | | | | | | | | | | | | | | | | | |
| .50 | | | | | | | | | | | | | | | | | |
| .75 | | | | | | | | | | | | | | | | | |
| 14.00 | | | | | | | | | | | | | | | | | |
| .25 | | | | | | | | | | | | | | | | | |
| .50 | | | | | | | | | | | | | | | | | |
| .75 | | | | | | | | | | | | | | | | | |
| 15.00 | | | | | | | | | | | | | | | | | |
| .25 | | | | | | | | | | | | | | | | | |
| .50 | | | | | | | | | | | | | | | | | |
| .75 | | | | | | | | | | | | | | | | | |
| 16.00 | | | | | | | | | | | | | | | | | |
| .25 | | | | | | | | | | | | | | | | | |
| .50 | | | | | | | | | | | | | | | | | |
| .75 | | | | | | | | | | | | | | | | | |
| 17.00 | | | | | | | | | | | | | | | | | |
| .25 | | | | | | | | | | | | | | | | | |
| .50 | | | | | | | | | | | | | | | | | |
| .75 | | | | | | | | | | | | | | | | | |
| 18.00 | | | | | | | | | | | | | | | | | |

カラー

| | | |
|--------------------|---|--|
| アリアーテ | ○ | |
| レイバン G15・G31・#3 | × | |
| 見本色 | × | |
| リラックス | × | |

原産国

日本

特殊加工

| | | |
|--------|----|----|
| 外径指定 | × | |
| プリズム | ○ | ※1 |
| 偏心 | × | |
| カーブ指定 | × | |
| UVカット | 標準 | ※2 |
| 厚み指定 | × | |
| 玉型カット | ○ | |
| スライス加工 | × | |

※1 3△まで可

※2 UV400