

## 仕様




屈折率	1.74
比重	1.47
アッペ数	33
設計	球面

## 対応コート

- つるつる
- ミラー (シルバー・ゴールド・ブルー・レッド)

## 製作範囲表

度数 (-)	球面	乱視 (-)															
		0.25	.50	.75	1.00	.25	.50	.75	2.00	.25	.50	.75	3.00	.25	.50	.75	4.00
0.00																	
.25																	
.50																	
.75																	
1.00																	
.25																	
.50																	
.75																	
2.00																	
.25																	
.50																	
.75																	
3.00																	
.25																	
.50																	
.75																	
4.00																	
.25																	
.50																	
.75																	
5.00																	
.25																	
.50																	
.75																	
6.00																	
.25																	
.50																	
.75																	
7.00																	
.25																	
.50																	
.75																	
8.00																	
.25																	
.50																	
.75																	
9.00																	
.25																	
.50																	
.75																	
10.00																	
.25																	
.50																	
.75																	
11.00																	
.25																	
.50																	
.75																	
12.00																	

			
	アクティブ ブラウン75	ナチュラル グレー75	ナチュラル グレー60
可視光線透過率	25%	25%	40%
偏光度	99%	99%	99%

印刷物と実際の商品の色調は多少異なります

## 特殊加工

外径指定	×	
プリズム	○	※1
偏心	○	※2
カーブ指定	×	
UVカット	標準	※3
厚み指定	×	
玉型カット	×	※4
スライス加工	×	

- ※1 3△まで可
- ※2 (プリズム換算) 3△まで可
- ※3 UV400
- ※4 組立加工は可 (玉型カットのみ不可)

## 原産国

日本

※注 ペア単位にてご注文ください。